

Lot 8993, Jalan Ikan Bawal, Telok Gong, 42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia Tel: 6-03-31341308, Fax: 6-03-31341994

MATERIAL SAFETY DATA SHEET

According to REACH-directive 1907/2006

July 01, 2020

1. Identification of the substance/preparation and of the Company/undertaking

Product Name : SILKFLEX ELASTIC RUBBER SATIN WHITE ERSW-001

Product Code : ERSW-001

Product Use : Textile Printing Auxiliary

Manufacturer : Silkflex Polymers Sdn. Bhd Lot
8993, Jalan Ikan Bawal, Telok

Gong,

42000 Pelabuhan Klang Selangor

Darul Ehsan : 6-03-31341803

Emergency telephone Number

2. Composition/information on hazard ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substance Directive 67/548/EEC and OSHA'S Hazard communication Standard, 29 OFR 1910.

Product Name	SILKFLEX ELASTIC RUBBER SATIN WHITE ERSW-001					
Composition	Chemical Type	pe CAS No. % By Weight				
Polymer	Acrylic 9003-01-4 40 - 60		40 - 60			
	Titanium Dioxide	13463-67-7	1696			
Pigment	Silicate B A	7631-86-9 A	D E S ²⁰ 1 ³⁰ L T			
	OIT 26530-20-1		Less than 0.00125 %			
Biocide	CMIT:MIT 3:1 55965-84-9		Less than 0.0008 %			
Others	Water and Additives	7732-18-5	20 - 30			

Occupational Exposure limit (s), if available, are listed in section.



Lot 8993, Jalan Ikan Bawal, Telok Gong, 42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia Tel: 6-03-31341308, Fax: 6-03-31341994

3. Hazards identification

Physical Chemical Hazards:Not applicable.Human health hazards:Not applicable.

1	Eirct	· aid	lme	2611	rac
-	пизи	. alu	шич	abu	

General: In all cases of doubt, or when symptoms persist, seek

medical attention. If unconscious, place in recovery position and seek medical advice. Never give anything by mouth to

an unconscious person.

Inhalation: Not applicable. Water-based and non-hazardous vapour.

Eye contact: Immediately irrigate copiously with clean water for 5-10

minutes, keeping eyelids open. Seek medical attention if

irritation persists.

Skin Contact: Remove contaminated clothes. Wash skin thoroughly with

soap and water or use a suitable skin cleaner. DO NOT use

solvent or thinners.

Ingestion: Keep person warm and at rest. DO NOT induce vomiting. If

washing hold down the head to reduce the risk of getting stomach content into the lungs. Obtain medical attention unless only an insignificant amount has been swallowed.

5. Fire fighting measures

Suitable:

The wet inks are not flammable. For dry inks, in case of fire, use water spray(fog), foam, dry chemicals or CO₂. Closed containers may be cooled with water spray.

Not suitable: Not applicable.

Hazardous thermal: Refer to MSDS Section 10.

decomposition Product

6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes. Avoid inhalation of vapors.

Refer to protective measures listed in sections 7 and 8.

Spill: Prevent entry into sewers, basements or confined areas,

dike etc. Put the spilled material in an appropriate waste

disposal.



Lot 8993, Jalan Ikan Bawal, Telok Gong, 42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia Tel: 6-03-31341308, Fax: 6-03-31341994

7. Handling and storage

Handling: Avoid contact with skin and eyes. Avoid excessive inhalation

of vapor. Eating and drinking should not be in area where this product is handled. Personal Protective Equipment, see section 8. Keep away from incompatibles in section 10.

Storage: Keep container tightly closed. Store in a dry, cool and well

ventilated area. Storage temperature: refer to the Technical Data Sheet. Keep away from incompatibles mentioned in

section 10.

Packaging material: Always keep in containers made from the same material

as the original one.

8. Exposure control/personal protection

Engineering measures: Provide exhaust ventilation or other engineering controls to

keep the airborne concentration of vapors below their respective Occupational Exposure limits. Ensure that eye wash station and safety showers are close to the workstation

location.

Hygiene measure: Wash hands, forearms and face thoroughly after handling

and before eating, smoking, using lavatory, and at the end of the day. Always immediately wash contaminated skin.

Apply a suitable skin lotion.

Personal protection equipment

Respiratory system:

Wear appropriate respirator when ventilation is

inadequate.

Eyes: Wear safety goggles or other suitable protective

equipment if there is a risk of contact.

Skin and body: Wear suitable protective clothing.

Hands: Wear suitable gloves.

9. Physical and chemical properties

Physical state: High viscosity white paste

Density: 1.25 g/cm³

Flash point: Not applicable (water-based)

Auto ignitions temperature: Not applicable (water-based)

Explosion limits: Not applicable (water-based)



Lot 8993, Jalan Ikan Bawal, Telok Gong, 42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia Tel: 6-03-31341308, Fax: 6-03-31341994

10.	Stabi	lity	and	reactivity
-----	-------	------	-----	------------

Stability: The product is stable.

Reactivity: Not reactive to oxidizing agents.

Hazardous thermal: These products are carbon oxides (CO,CO₂).

Decomposition products

11. Toxicological Information

In poorly ventilated places, inhalation of vapor may

cause irritation of the respiratory system.

Eye contact: Can cause irritation and temporary damage if splashes

come in contact with the eye.

Skin Contact: Repeated or prolonged contact with the preparation may

cause removal of natural fat from the skin, resulting in non-

allergic contact dermatitis.

Ingestion: Ingestion may cause stomach pains and vomiting

12. Ecological information

Eco-Toxicity: Complies with GOTS, REACH and Oeko-Tex.

13. Disposal Considerations

European Waste:
Catalogues (EWC)

Hazardous Waste: To the present knowledge of the supplier, this product

is not regarded as hazardous waste as defined by EU

Directive 91/689/EC.

Methods of disposal: Do not allow to enter drains or water course. Ship for

treatment/ disposal in accordance with local regulations.

14. Transport information

UN Number: Not regulated

15. Regulatory Information



SILKFLEX POLYMERS SDN BHD (545022-T) Lot 8993, Jalan Ikan Bawal, Telok Gong, 42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia Tel: 6-03-31341308, Fax: 6-03-31341994

Classification

This product is not classified according to the EU **Risk Phrases:**

regulations

Safety Phrases: Not applicable.

Other Information

Additional warning: Safety Date Sheet available for professional user on

request.

Restriction to market: Not applicable.

Directive

16. Other information

Not applicable.

The information in this brochure has been compiled in accordance to our best knowledge at the date of issue and is based on recent technological and scientific developments. However, this information should not be construed as recommending the use of our product in violation of any patent or as warranties (express or implied) of non-infringement or its fitness for any particular purpose. Prospective purchasers are invited to conduct their own tests and studies to determine the fitness of Silkflex products for their particular purposes and specific applications. Due to the varying techniques and conditions applied, Silkflex accepts no responsibility for any use of the product, by way of experiment or manufacture nor does Silkflex accept any responsibility for the used techniques in any application whatsoever. Silkflex does not warrant against infringement of patents of third parties by reason of any uses purchasers make of the product.

